

# Multi-Conductor Unshielded Cable

## Audio Control Cable UL, CM, CSA AWM CMG

**Conductors:** Stranded Tin-Plated Copper  
**Insulation:** SR-PVC  
**Jacket:** Gray PVC  
**Construction:** Conductors Cabled  
**Temperature Rating:** UL 80°C, CSA 105°C  
**Operating Voltage:** 300 Volts UL, 600 Volts CSA  
**Applications:** For point to point wiring of computers, control systems, electronic apparatus and panels.  
**Approvals:** UL, CM  
 CSA AWM II A/B, CMG FT4



TEVELEC NUMBER	No. of Conds.	AWG Size	Stranding	Nominal Insulation	Nominal Jacket	Nominal O.D.	Color Chart	Weight Lbs/1000'
T5268	2	12	65	.030	.030	.400	2	95
T5269	3	12	65	.030	.030	.428	2	130
T5270	4	12	65	.030	.030	.471	2	165
T5271	5	12	65	.030	.030	.487	2	177
T5273	7	12	65	.030	.050	.602	2	262
T5279	2	10	105	.030	.030	.464	Blk/Red	134

## Station 'Z' Wire CSA CMG FT4

**Conductors:** Solid Bare Copper  
**Insulation:** SR-PVC  
**Jacket:** PVC  
**Construction:** Insulated conductors cabled and jacketed.  
**Temperature Rating:** CSA 60°C  
**Colour Code Chart:** 7  
**Applications:** For wiring residential telephone lines (POTS), and for security control wiring in residential and commercial applications.  
**Approvals:** CSA CMG, FT4



TEVELEC NUMBER	No. of Conds.	AWG Size	Stranding	Nominal Insulation	Nominal Jacket	Nominal O.D.	Weight Lbs/1000'
T3992	2	22	Solid	.007	.018	.114	9
T3993	3	22	Solid	.007	.018	.120	12
T3994	4	22	Solid	.007	.020	.130	15
T3996	6	22	Solid	.007	.020	.160	25
T3998	8	22	Solid	.007	.023	.175	31
T3990	10	22	Solid	.007	.023	.190	37
T3999	12	22	Solid	.007	.023	.210	44