

Multi-Conductor Unshielded Cable

Low Voltage Thermostat CSA CMG

Conductors: Solid Bare Copper
Insulation: PVC
Jacket: Brown PVC, (Other colors available).
Construction: Conductors cabled except where noted. (Flat items are parallel conductors).
Temperature Rating: 60°C
Color Code Chart: 11
Operating Voltage: 30 Volts
Applications: Thermostat controls, door bells, security systems and other low voltage remote control systems where voltage does not exceed 30 volts.
Approvals: CSA LVT CMG FT4



| TEVELEC NUMBER | No. of Conds. | AWG Size | Stranding | Nominal Insulation | Nominal Jacket | Nominal O.D. | Weight Lbs/1000' |
|----------------|---------------|----------|-----------|--------------------|----------------|--------------|------------------|
| T2149 | 2 Flat | 18 | Solid | .015 | .030 | .143 X .213 | 26 |
| T2150 | 2 | 18 | Solid | .015 | .030 | .213 | 26 |
| T2151 | 3 | 18 | Solid | .015 | .030 | .225 | 33 |
| T2152 | 4 | 18 | Solid | .015 | .030 | .232 | 40 |
| T2153 | 5 | 18 | Solid | .015 | .030 | .243 | 51 |
| T2154 | 6 | 18 | Solid | .015 | .030 | .261 | 58 |
| T2156 | 8 | 18 | Solid | .015 | .030 | .292 | 81 |
| T2158 | 10 | 18 | Solid | .015 | .030 | .320 | 100 |
| T2170 | 2 Flat | 16 | Solid | .015 | .030 | .166 X .224 | 48 |
| T2173 | 4 | 16 | Solid | .015 | .030 | .258 | 61 |